

PV-500EVO2



Full HD 3"

DVR

H.264!



Feature

- * Real 1080P,
- * H.264
- * 3.0" TFT LCD
- * 16:9
- * 1.3M / 2M
- * 1/3"
- * 1.5M
- * 1.5M



PI-PV800




IR

S-USB/PV-500



USB Cable

CHG-0520



DC 5V

PT-PV800



S-EP/PV500




Earphone

BA-2200



2200mA Battery

S-PJ2R-5V



AV In Cable

S-1R3R/PV-500



AV Out Cable

Q-PI-WSD10




Cable Controller

S-MINI HDMI(WDS)



Controller Cable

Specification



Item Number	PV-500EVO2	
	3.0" 960 x 240 TFT LCD	
	NTSC/ PAL	
	NTSC/ PAL (1.3Mega) / (2Mega)	
	/	
	320x240 to Max 1920x1080	
	Above 720P (1280x960) 1080P(1920x1080)	
	SD Card (Supports up to 32GB SDHC)	
	1, 5, 10, 15, 25, 30 fps	
DC5V to 2.5 phone jack	300mA Max	
DC3.3V to mini-HDMI	250mA Max	
	USB2.0	
(Bit rate)	In Standard 720x576@25 FPS (PAL) High (5Mbps) / Medium (3.3Mbps) / Low (2.5Mbps) Adjustable	
/	YYYY/MM/DD (America) , HH,MM,SS (U.K.)	
	Yes	
	JPEG	
	480mA	600mA
	200 (BA-2200)	
	85X54X17	
	71 .	

BCM-DU01



BA-4400



4400mA Battery